





CONEXIÓN TUERCA LOCA JIC 37°



D			ROSCA	A	B	H	REFERENCIA
Tamaño	DN	Pulgadas		mm	mm	mm	EX
4	6	1/4	7/16" - 20 UNF	41,5	13,5	15,0	4EX4FJX
4	6	1/4	1/2" - 20 UNF	43,7	15,7	17,0	4EX5FJX
4	6	1/4	9/16" - 18 UNF	43,7	15,7	19,0	4EX6FJX
6	10	3/8	9/16" - 18 UNF	45,7	15,7	19,0	6EX6FJX
6	10	3/8	3/4" - 16 UNF	48,5	18,5	24,0	6EX8FJX
6	10	3/8	7/8" - 14 UNF	50,0	20,0	27,0	6EX10JX
8	12	1/2	3/4" - 16 UNF	51,0	19,0	24,0	8EX8FJX
8	12	1/2	7/8" - 14 UNF	53,0	21,0	27,0	8EX10FJX
8	12	1/2	1.1/16" - 12 UNF	53,0	21,0	32,0	8EX12FJX
10	16	5/8	7/8" - 14 UNF	55,5	21,0	27,0	10EX10FJX
10	16	5/8	1.1/16" - 12 UNF	55,5	21,0	32,0	10EX12FJX
12	20	3/4	1.1/16" - 12 UNF	61,1	21,6	32,0	12EX12FJX
12	20	3/4	1.5/16" - 12 UNF	62,7	23,2	38,0	12EX16FJX
16	25	1	1.5/16" - 12 UNF	77,7	24,2	38,0	16EX16FJX




CONEXIÓN MACHO JIC 37°



D			ROSCA	A	B	H	REFERENCIA
Tamaño	DN	Pulgadas		mm	mm	mm	mm
4	6	1/4	7/16" - 20 UNF	54,5	26,5	12,0	4EX4MJ
4	6	1/4	1/2" - 20 UNF	55,5	27,5	14,0	4EX5MJ
4	6	1/4	9/16" - 18 UNF	55,5	27,5	15,0	4EX6MJ
6	10	3/8	9/16" - 18 UNF	58,0	28,0	15,0	6EX6MJ
6	10	3/8	3/4" - 16 UNF	63,0	33,0	19,0	6EX8MJ
6	10	3/8	7/8" - 14 UNF	66,0	36,0	24,0	6EX10MJ
8	12	1/2	3/4" - 16 UNF	65,5	33,5	19,0	8EX8MJ
8	12	1/2	7/8" - 14 UNF	68,5	36,5	24,0	8EX10MJ
8	12	1/2	1.1/16" - 12 UNF	70,5	38,5	27,0	8EX12MJ
10	16	5/8	7/8" - 14 UNF	74,0	36,5	24,0	10EX10MJ
10	16	5/8	1.1/16" - 12 UNF	73,0	38,5	27,0	10EX12MJ
12	20	3/4	1.1/16" - 12 UNF	79,0	39,5	27,0	12EX12MJ
16	25	1	1.5/16" - 12 UNF	97,0	43,5	34,0	16EX16MJ




CONEXIÓN TUERCA LOCA CODO 90° JIC 37°



D			ROSCA	A	B	E	H	Referencia
Tamaño	DN	Pulgadas		mm	mm	mm	mm	EX
4	6	1/4	7/16" - 20 UNF	49,0	21,0	26,5	15,0	4EX4FJX90S
4	6	1/4	1/2" - 20 UNF	59,0	31,0	29,5	17,0	4EX5FJX90S
4	6	1/4	9/16" - 18 UNF	49,5	21,5	28,0	19,0	4EX6FJX90S
6	10	3/8	9/16" - 18 UNF	60,5	60,5	33,5	19,0	6EX6FJX90S
6	10	3/8	3/4" - 16 UNF	62,0	32,0	34,5	24,0	6EX8FJX90S
8	12	1/2	3/4" - 16 UNF	72,5	40,5	43,0	24,0	8EX8FJX90S
8	12	1/2	7/8" - 14 UNF	73,5	41,5	42,5	27,0	8EX10FJX90S
8	12	1/2	1.1/16" - 12 UNF	71,0	39,0	47,0	32,0	8EX12FJX90S
10	16	5/8	7/8" - 14 UNF	78,5	44,0	47,0	27,0	10EX10FJX90S
10	16	5/8	1.1/16" - 12 UNF	81,5	47,0	48,0	32,0	10EX12FJX90S
12	20	3/4	1.1/16" - 12 UNF	89,5	50,0	50,0	32,0	12EX12FJX90S
16	25	1	1.5/16" - 12 UNF	122,0	68,5	70,0	38,0	16EX16FJX90S



CONEXIÓN TUERCA LOCA CODO 45° JIC 37°



D			ROSCA	A	B	E	H	Referencia
Tamaño	DN	Pulgadas		mm	mm	mm	mm	EX
4	6	1/4	7/16" - 20 UNF	66,0	38,0	15,0	15,0	4EX4FJX45S
4	6	1/4	1/2" - 20 UNF	68,0	40,0	17,0	17,0	4EX5FJX45S
4	6	1/4	9/16" - 18 UNF	68,0	40,0	17,0	19,0	4EX6FJX45S
6	10	3/8	9/16" - 18 UNF	83,0	53,0	18,0	19,0	6EX6FJX45S
6	10	3/8	3/4" - 16 UNF	84,0	54,0	19,0	24,0	6EX8FJX45S
8	12	1/2	3/4" - 16 UNF	94,0	62,0	20,0	24,0	8EX8FJX45S
8	12	1/2	7/8" - 14 UNF	95,0	63,0	21,0	27,0	8EX10FJX45S
8	12	1/2	1.1/16" - 12 UNF	94,5	60,0	22,0	27,0	8EX12FJX45S
10	16	5/8	1.1/16" - 12 UNF	97,5	63,0	25,0	32,0	10EX12FJX45S
12	20	3/4	1.1/16" - 12 UNF	101,5	62,0	29,0	32,0	12EX12FJX45S
16	25	1	1.5/16" - 12 UNF	142,0	88,5	39,5	38,0	16EX16FJX45S