





CONEXIÓN TUERCA LOCA DIN2353 SERIE S



D			ROSCA	A	B	H	REFERENCIA
Tamaño	DN	Pulgadas		mm	mm	mm	EX
4	6	1/4	M14x1,5 - 6S	53,7	25,7	17,0	4EX6FDHORX
4	6	1/4	M16x1,5 - 8S	53,8	25,8	19,0	4EX8FDHORX
4	6	1/4	M18x1,5 - 10S	54,0	26,0	22,0	4EX10FDHORX
5	8	5/16	M20x1,5 - 12S	54,4	26,5	24,0	5EX12FDHORX
6	10	3/8	M18x1,5 - 10S	56,5	26,5	22,0	6EX10FDHORX
6	10	3/8	M20x1,5 - 12S	56,5	26,5	24,0	6EX12FDHORX
6	10	3/8	M22x1,5 - 14S	59,5	29,5	27,0	6EX14FDHORX
8	12	1/2	M22x1,5 - 14S	60,0	28,0	27,0	8EX14FDHORX
8	12	1/2	M24x1,5 - 16S	63,0	31,0	30,0	8EX16FDHORX
10	16	5/8	M30x2 - 20S	71,0	36,5	36,0	10EX20FDHORX
12	20	3/4	M30x2 - 20S	75,5	36,0	36,0	12EX20FDHORX
12	20	3/4	M36x2 - 25S	77,6	38,1	46,0	12EX25FDHORX
16	25	1	M36x2 - 25S	93,0	39,5	46,0	16EX25FDHORX
16	25	1	M42x2 - 30S	95,1	41,6	50,0	16EX30FDHORX




CONEXIÓN MACHO DIN2353 SERIE S



D			ROSCA	A	B	H	REFERENCIA
Tamaño	DN	Pulgadas		mm	mm	mm	mm
4	6	1/4	M16x1,5 - 8S	53,5	25,5	17,0	4EX8MDH
4	6	1/4	M18x1,5 - 10S	54,5	26,5	19,0	4EX10MDH
5	8	5/16	M20x1,5 - 12S	55,0	27,0	22,0	5EX12MDH
6	10	3/8	M18x1,5 - 10S	57,0	27,0	19,0	6EX10MDH
6	10	3/8	M20x1,5 - 12S	57,0	27,0	22,0	6EX12MDH
6	10	3/8	M22x1,5 - 14S	59,0	29,0	22,0	6EX14MDH
8	12	1/2	M24x1,5 - 16S	62,5	30,5	24,0	8EX16MDH
10	16	5/8	M30x2 - 20S	68,0	33,5	30,0	10EX20MDH
12	20	3/4	M30x2 - 20S	73,5	34,0	30,0	12EX20MDH
12	20	3/4	M36x2 - 25S	77,2	37,7	36,0	12EX25MDH
16	25	1	M36x2 - 25S	92,0	38,5	36,0	12EX25MDH
16	25	1	M42x2 - 30S	94,0	40,5	46,0	16EX30MDH




CONEXIÓN TUERCA LOCA CODO 90° DIN2353 SERIE S



D			ROSCA	A	B	E	H	Referencia
Tamaño	DN	Pulgadas		mm	mm	mm	mm	EX
4	6	1/4	M16x1,5 - 8S	53,5	25,5	31,0	19,0	4EX8FDHORX90
4	6	1/4	M18x1,5 - 10S	57,0	29,0	29,0	22,0	4EX810DHORX90
5	8	5/16	M20x1,5 - 12S	56,5	28,5	33,0	24,0	5EX12FDHORX90
6	10	3/8	M18x1,5 - 10S	63,5	33,5	33,5	22,0	6EX10FDHORX90
6	10	3/8	M20x1,5 - 12S	63,5	33,5	33,5	24,0	6EX12FDHORX90
6	10	3/8	M22x1,5 - 14S	63,5	33,5	42,0	27,0	6EX14FDHORX90
8	12	1/2	M24x1,5 - 16S	73,0	41,0	43,0	30,0	8EX16FDHORX90
10	16	5/8	M30x2 - 20S	82,5	48,0	48,0	36,0	10EX20FDHORX90
12	20	3/4	M30x2 - 20S	89,5	50,0	48,0	36,0	12EX20FDHORX90
12	20	3/4	M36x2 - 25S	89,5	50,0	58,0	46,0	12EX25FDHORX90
16	25	1	M36x2 - 25S	126,5	73,0	70,0	46,0	16EX25FDHORX90
16	25	1	M42x2 - 30S	126,5	73,0	70,0	50,0	16EX30FDHORX90



CONEXIÓN TUERCA LOCA CODO 45° DIN2353 SERIE S



D			ROSCA	A	B	E	H	Referencia
Tamaño	DN	Pulgadas		mm	mm	mm	mm	EX
4	6	1/4	M16x1,5 - 8S	78,0	50,0	17,0	19,0	4EX8FDHORX45
4	6	1/4	M18x1,5 - 10S	76,5	48,5	17,0	22,0	4EX810DHORX45
5	8	5/16	M20x1,5 - 12S	78,0	50,0	20,0	24,0	5EX12FDHORX45
6	10	3/8	M18x1,5 - 10S	87,0	57,0	17,0	22,0	6EX10FDHORX45
6	10	3/8	M20x1,5 - 12S	87,0	57,0	17,0	24,0	6EX12FDHORX45
6	10	3/8	M22x1,5 - 14S	87,0	59,0	19,0	27,0	6EX14FDHORX45
8	12	1/2	M24x1,5 - 16S	98,5	66,5	22,0	30,0	8EX16FDHORX45
10	16	5/8	M30x2 - 20S	99,0	64,5	26,0	36,0	10EX20FDHORX45
12	20	3/4	M30x2 - 20S	103,5	64,0	27,0	36,0	12EX20FDHORX45
12	20	3/4	M36x2 - 25S	109,5	70,0	28,0	46,0	12EX25FDHORX45
16	25	1	M36x2 - 25S	142,0	88,5	38,0	46,0	16EX25FDHORX45
16	25	1	M42x2 - 30S	142,5	89,0	38,0	50,0	16EX30FDHORX45